We focus on your needs
Your reliable service
Your loyal friend

Taizhou Taili Drill Press Co., Ltd.

Add: Tangwang Industrial Zone Pengjie Luqiao Taizhou Zhejiang 318050 China
Tel: 0086-576-82583228 82581128
Fax: 0086-576-82583228
E-mail: sales@drillmachine.cn sales1@drillmachine.cn
http: //www.drillmachine.cn

www.drillmachine.cn

台州市泰立台钻制造有限公司
Taizhou Taili Drill Press Co., Ltd.

The Quality Is Our Root,the Quality Is Our Future

Drill Press Sanding Machine
Industrial Drilling & Tapping Machine

2015

www.drillmachine.cn

BRIEF
INTRODUCTION

Taizhou Taili Drill Press Co., LTD is located in the Luqiao District, Taizhou City, in southern Zheijiang Province. Our company is 5 kilometers from the Luqaio airport and 15 kilometers from taizhou port, near national highway no. 104, with convenient transportation.

As of 2015, we have 125 employees in total. Employees include 5 designers, 7 production testers, and 4 salesmen. Our company has 12,000 square meters of total area, factory and offices make up 8500 square meters. We have 55 pieces of machining equipment and 25 quality testing instruments.

We apply computer technology to our management process, production and manufacturing, after-sales customer service, quality control and other administrative activities. We have established networks of information about our material resources that provide fast, efficient, accurate and secure information.

We abide by strict quality control measures in our production,manufacturing and after-sales support. All of our products have passed "ISO 9001: 2000 quality control system." certification. Our products comply with relevant safety standards and requirements. We are very competent in ODM/OEM product development.

Our competitive power is rooted in and guaranteed by the rule of "innovation brings a splendid future, giving first priority to quality". We have knowledgeable and energetic employees to assure our product quality. Our company sales have increased rapidly since 2003;we sell our products to America, Canada, Europe, Australia, and other countries; about 27 countries in total.

The customer is king! We hope to cooperate with worldwide partners on the basis of mutual benefit.

TMT
TianLi

Win the market by the quality
Makes the quality with the advanced equipment
Complete hardware equipment
Assembly line production pattern
Standardized managerment
Professional technical personnel
Generation upon generation of
masterpiece products of achievement

DP系列 DP SERIES

DP20013B

DP20013A

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

Cast-iron Handle



2.5inch Vice

External Light

Halogen Lamp&Cross Laser

Strong Ruber Handle

型号: Model	DP20013B	DP20013A
钻孔能力: Drill Capacity	13mm	13mm
夹头范围: Chuck Capacity	13mm	13mm
旋径: Swing	8"(200mm)	8"(200mm)
锥度: Spindle Taper	B16/JT33	B16/JT33
转速范围(50Hz): Speed Range	5(500-2500)	5(500-2500)
转速范围 (60Hz): Speed Range	5(620-3100)	5(620-3100)
主轴行程: Spindle Travel	50mm	50mm
立柱直径: Column Diameter	48mm	48mm
齿条: Rack & Pinion	NO	NO
底座尺寸: Base Size	280*180mm	280*180mm
工作台尺寸: Table Size	165 × 165mm	165 × 165mm
电机功率: Motor	300W	300W
机器总高: Overall Height	580mm	580mm
净毛重: N.W. / G.W.	15/17kgs	15/17kgs
包装尺寸: Packing Size	470*240*350mm	470*240*350mm
20尺装柜量: Units Per 20' Container	850pcs	850pcs

DP系列 DP SERIES

DP25013B

DP25016B

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

Cast-iron Handle



2.5inch Vice

External Light

Halogen Lamp&cross Laser

Strong Ruber Handle

型号: Model	DP25013B	DP25016B
钻孔能力: Drill Capacity	13mm	16mm
夹头范围: Chuck Capacity	13mm	16mm
旋径: Swing	10"(250mm)	10"(250mm)
锥度: Spindle Taper	B16/JT33	MT2
转速范围(50Hz): Speed Range	5(500-2500)	5(500-2500)/12(180-2740)
转速范围 (60Hz): Speed Range	5(620-3100)	5(620-3100)/12(250-3100)
主轴行程: Spindle Travel	60mm	60mm
立柱直径: Column Diameter	59.5mm	59.5mm
齿条: Rack & Pinion	NO	YES
底座尺寸: Base Size	348*215mm	348*215mm
工作台尺寸: Table Size	195*196mm	195*196mm
电机功率: Motor	400W	400W
机器总高: Overall Height	720mm	850mm
净毛重: N.W. / G.W.	28/30	30/33
包装尺寸: Packing Size	550*370*254mm	690*430*260mm
20尺装柜量: Units Per 20' Container	540pcs	400pcs

DP系列 DP SERIES

DP33016B

DP33016F

型号: Model	DP33016B	DP33016F
钻孔能力: Drill Capacity	16mm	16mm
夹头范围: Chuck Capacity	16mm	16mm
旋径: Swing	13"(330mm)	13"(330mm)
锥度: Spindle Taper	MT2	MT2
转速范围(50Hz): Speed Range	12(180-2740)	12(180-2740)
转速范围 (60Hz): Speed Range	12(250-3100)	12(250-3100)
主轴行程: Spindle Travel	80mm	80mm
立柱直径: Column Diameter	73mm	73mm
齿条: Rack & Pinion	YES	YES
底座尺寸: Base Size	450*280mm	456*280mm
工作台尺寸: Table Size	254*254mm	254*254mm
电机功率: Motor	600W	600W
机器总高: Overall Height	990mm	1630mm
净毛重: N.W. / G.W.	52/56kgs	55/60kgs
包装尺寸: Packing Size	895*490*290mm	1430*510*256mm
20尺装柜量: Units Per 20' Container	224pcs	160pcs

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

Cast-iron Handle

3inch Vice



Round Table

Halogen Lamp&cross Laser

Strong Ruber Handle

DP系列 DP SERIES

DP38016B

DP38016F

型号: Model	DP38016B	DP38016F
钻孔能力: Drill Capacity	20mm	20mm
夹头范围: Chuck Capacity	16mm	16mm
旋径: Swing	15"(380mm)	15"(380mm)
锥度: Spindle Taper	MT2	MT2
转速范围(50Hz): Speed Range	12(180-2740)	12(180-2740)
转速范围 (60Hz): Speed Range	12(250-3100)	12(250-3100)
主轴行程: Spindle Travel	80mm	80mm
立柱直径: Column Diameter	73mm	73mm
齿条: Rack & Pinion	YES	YES
底座尺寸: Base Size	480*290mm	480*290mm
工作台尺寸: Table Size	305*305mm	305*305mm
电机功率: Motor	600W	600W
机器总高: Overall Height	1050mm	1635mm
净毛重: N.W. / G.W.	58/63kgs	64/69kgs
包装尺寸: Packing Size	895*490*290mm	1430*510*256mm
20尺装柜量: Units Per 20' Container	224pcs	160pcs

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

L-R Switch

4inch Vice



Square Table

Light

Strong Ruber Handle

DP系列 DP SERIES

DP43016F

型号: Model	DP43016F
钻孔能力: Drill Capacity	25mm
夹头范围: Chuck Capacity	16/20mm
旋径: Swing	17"(430mm)
锥度: Spindle Taper	MT2//MT3
转速范围(50Hz): Speed Range	16(160-3000)
转速范围 (60Hz): Speed Range	16(200-3630)
主轴行程: Spindle Travel	80mm
立柱直径: Column Diameter	80mm
齿条: Rack & Pinion	YES
底座尺寸: Base Size	505*345mm
工作台尺寸: Table Size	356*356mm
电机功率: Motor	1100W
机器总高: Overall Height	1635mm
净毛重: N.W. / G.W.	81/86kgs
包装尺寸: Packing Size	1410*540*250mm
20尺装柜量: Units Per 20' Container	144pcs

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

Cast-iron Handle

L-R Switch



5inch Vice

Arbor MT3-MT2



Round Table

Square Table

Light

DP系列 DP SERIES

DP51020F

型号: Model	DP51020F
钻孔能力: Drill Capacity	32mm
夹头范围: Chuck Capacity	20mm
旋径: Swing	20"(510mm)
锥度: Spindle Taper	MT3/MT4
转速范围(50Hz): Speed Range	12(120-3480)
转速范围 (60Hz): Speed Range	12(150-4200)
主轴行程: Spindle Travel	120mm
立柱直径: Column Diameter	92mm
齿条: Rack & Pinion	YES
底座尺寸: Base Size	580*420mm
工作台尺寸: Table Size	475*425mm
电机功率: Motor	1500W
机器总高: Overall Height	1710mm
净毛重: N.W. / G.W.	132/135kgs
包装尺寸: Packing Size	1450*653*333mm
20尺装柜量: Units Per 20' Container	93pcs

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

Cast-iron Handle

L-R Switch



5inch Vice

Arbor Mt4-mt3

2-step Switch

Cooling System

Light

RDP系列 RDP SERIES

RDP86016B

RDP86016F

MORTISING KIT ATTACHMENT

KEY FEATURES

- Simple attachment to the drill press
- Robust cast iron holder and fence
- Large 3" capacity under hold down
- Large 3-1/2" capacity from ends of clamp rods to fence
- Mounting sleeves: 2.945"×2.6", 2.6"×2.366", 2.366"×2.17"
- Mounting bushings: 2.6"×1.57", 2.6"×1.88", 2.6"×2.00"
- Mortising chisels & bits: 1/4", 5/16", 3/8", 1/2" (3/4" shank od)

型号: Model	RDP86016B	RDP86016F
钻孔能力: Drill Capacity	16mm	16mm
夹头范围: Chuck Capacity	16mm	16mm
旋径: Swing	34"(860mm)	34"(860mm)
锥度: Spindle Taper	MT2	MT2
转速范围(50Hz): Speed Range	5 (500-2500)	5 (500-2500)
转速范围(60Hz): Speed Range	5 (620-3100)	5 (620-3100)
主轴行程: Spindle Travel	80mm	80mm
主轴箱旋转: Head Tilt	45° R-90° L	45° R-90° L
工作台尺寸: Table Size	285*220mm	Φ300mm
工作台旋转: Table Tilt	45°	45°
立柱直径: Column Diameter	59.5mm	73mm
齿条: Rack & Pinion	YES	YES
底座尺寸: Base Size	350*215mm	456*280mm
机器总高: Overall Height	810mm	1630mm
电机功率: Motor	400W	400W
净毛重: N.W. / G.W.	40/44kgs	58/62kgs
包装尺寸: Packing Size	910*360*320mm	1400*490*250mm
20尺装柜量: Units Per 20' Container	266pcs	160pcs

DP系列 DP SERIES

可选配件 OPTIONAL ACCESSORIES

Keyless Chuck

Cast-iron Handle



3inch Vice



Round Table

Black Chromed Scale

Special Guard

Slide Cover

Emergency Stop Switch

专业系列 PRO SERIES

- 单独急停开关
- 正反转开关
- 镀暗铬手柄杆及手柄座
- 高度可调节并带微动开关的护镜
- 自紧式夹头可选

- Separate Emergency- stop switch
- Switch for right-/left-hand rotation
- Handles and the seat are treated in black chrome
- Height-adjustable screeing grid with micro switch
- Optional keyless chuck

DP13

DP16

DP20/F

DP20/B

专业系列 PRO SERIES

DP25/F

DP28

DP35

emergency stop



special guard

DP25/B

RB系列 RB SERIES

The German Brand

RB13

RB14

型号: Model	RB13	RB14
钻孔能力: Drill Capacity	13mm	13mm
旋径:Swing	210mm	210mm
锥度: Spindle Taper	B16	B16
转速范围(50Hz): Speed Range	580-2700 rpm	580-2700 rpm
主轴行程: Spindle Travel	50mm	50mm
立柱直径: Column Diameter	48mm	48mm
底座尺寸: Base Size	330*190mm	330*190mm
工作台尺寸: Table Size	Φ170mm	Φ170mm
电机功率: Motor	300W	300W
机器总高: Overall Height	580mm	620mm
灯: LED	NO	YES
净毛重: N.W. / G.W.	14/15 kgs	15/16 kgs
包装尺寸: Packing Size	490*370*250mm	530*370*250mm
20尺装柜量: Units Per 20' Container	660 pcs	600pcs

RB系列 RB SERIES

RB18

型号: Model	RB18 VARIO RB18 无级变速
钻孔能力: Drill Capacity	16mm
旋径:Swing	224mm
锥度: Spindle Taper	MT2
转速范围(50Hz): Speed Range	310-880/880-2400 rpm
主轴行程: Spindle Travel	50mm
立柱直径: Column Diameter	58.5mm
底座尺寸: Base Size	435*250mm
工作台尺寸: Table Size	Φ220mm
电机功率: Motor	400W
机器总高: Overall Height	750mm
灯: LED	YES
净毛重: N.W. / G.W.	29/30 kgs
包装尺寸: Packing Size	665*390*295mm
20尺装柜量: Units Per 20' Container	406 pcs

数显无级调速钻床 VARIABLE SPEED DRILL PRESS

DP30016B-VS

型号: Model	DP30016B-VS
钻孔能力: Drill Capacity	16mm
夹头范围: Chuck Capacity	16mm
旋径: Swing	12"(300mm)
锥度: Spindle Taper	MT2
转速范围(50Hz): Speed Range	360-3500
转速范围 (60Hz): Speed Range	450-4000
主轴行程: Spindle Travel	90mm
立柱直径: Column Diameter	59.5mm
齿条: Rack & Pinion	YES
底座尺寸: Base Size	413*246mm
工作台尺寸: Table Size	243×243mm
电机功率: Motor	550W
机器总高: Overall Height	910mm
净毛重: N.W. / G.W.	43/46kgs
包装尺寸: Packing Size	700*510*270mm
20尺装柜量: Units Per 20' Container	300pcs

产品特写 KEY FEATURE

Speed Adjust Handle

Extension Table

90mm Travel

Speed Display

Speed Change Device

Led & Cross Laser

VARIABLE SPEED DRILL PRESS TaiLI

数显无级调速钻床 VARIABLE SPEED DRILL PRESS

DP43016F-VS

型号: Model	DP43016F-VS
钻孔能力: Drill Capacity	16mm
夹头范围: Chuck Capacity	16mm
旋径: Swing	17"(430mm)
锥度: Spindle Taper	MT2
转速范围(50Hz): Speed Range	410-2100
转速范围 (60Hz): Speed Range	500-2600
主轴行程: Spindle Travel	150mm
立柱直径: Column Diameter	80mm
齿条: Rack & Pinion	YES
底座尺寸: Base Size	580*420mm
工作台尺寸: Table Size	356×356mm
电机功率: Motor	1100W
机器总高: Overall Height	1820mm
净毛重: N.W. / G.W.	105/95kgs
包装尺寸: Packing Size	1530*700*280mm
20尺装柜量: Units Per 20' Container	88pcs

产品特写 KEY FEATURE

Speed Adjust Handle

150mm Travel

Speed Change Device

Speed Display

Led Light

Special Guard

工业级系列 INDUSTRIAL SERIES

优质高效与高性价比

- 厚重结实铸铁制造
- 立柱大尺寸 壁厚 运转平稳 性能稳定
- 主轴经热处理，精加工同心度高
- 可锁式主开关
- 钻夹头防护罩 高度可调节并带微动开关
- Convincing arguments:qulity efficiency and price
- Heavy,solid cast iron construction
- Smooth running and stability due to a largely dimensioned thick-walled steel colomn
- High concentricity precision due to heat treatment and ground work spindle
- Lockable main switch and protective motor switch
- Height-adjustable screeing grid with micro switch

Z1513B

Z1513A

型号: Model	Z1513A	Z1513B
功能: Feature	Drilling	Drilling
钻孔/攻丝范围: Drill/Tapping Capacity	13mm	13mm
夹头: Chuck Capacity	1~13mm	1~13mm
立柱直径: Column Diameter	70mm	70mm
主轴行程: Spindle Travel	80mm	80mm
旋径: Swing	360mm	360mm
主轴到工作台最大距离: Max. Distance spindle to table	340mm	340mm
主轴到底座最大距离: Max. Distance spindle to base	570mm	570mm
主轴锥度: Spindle Taper	B16	B16
转速范围: Speed Range	360～2700RPM	360～2700RPM
速度: No. of Speed	5	5
工作台尺寸: Table Size	267X230mm	267X230mm
底座尺寸: Base Size	490*318mm	490*318mm
机器总高: Overal Height	1000mm	1000mm
电机功率: Motor	400V/550W/50Hz	400V/550W/50Hz
重量: Weight	85KG	85KG
包装尺寸: Packing Size	680X380X930mm	680X380X930mm

工业级系列 INDUSTRIAL SERIES

Z1520F

型号: Model	Z1520F
功能: Feature	Drilling
钻孔/攻丝范围: Drill/Tapping Capacity	16mm
夹头: Chuck Capacity	1~16mm
立柱直径: Column Diameter	73mm
主轴行程: Spindle Travel	80mm
旋径: Swing	360mm
主轴到工作台最大距离: Max. Distance spindle to table	790mm
主轴到底座最大距离: Max. Distance spindle to base	1125mm
主轴锥度: Spindle Taper	B16
转速范围: Speed Range	360～2700RPM
速度: No. of Speed	5
工作台尺寸: Table Size	280X280mm
底座尺寸: Base Size	520*345mm
机器总高: Overal Height	1550mm
电机功率: Motor	400V/550W/50Hz
重量: Weight	108KG
包装尺寸: Packing Size	740X410X1720mm

产品特写 KEY FEATURE



Special Guard

Strong Ruber Handle

Locking Device

Keyless Chuck

工业级系列 INDUSTRIAL SERIES

优质高效与高性价比

- 立柱大尺寸 壁厚 运转平稳 性能稳定
- 主轴经热处理，精加工同心度高
- 可锁式主开关
- 钻夹头防护罩 高度可调节并带微动开关

- Heavy,solid cast iron construction
- Smooth running and stability due to a largely dimensioned thick-walled steel colomn
- High concentricity precision due to heat treatment and ground work spindle
- Lockable main switch and protective motor switch
- Height-adjustable screeing grid with micro switch

产品特写 KEY FEATURE

Tapping Device

Special Guard

Z1720B

型号: Model	Z1720B	ZS1720B
功能: Feature	Drilling	Drilling & Tapping
钻孔/攻丝范围: Drill/Tapping Capacity	16mm	16mm/M12
夹头: Chuck Capacity	3~16mm	3~16mm
立柱直径: Column Diameter	70mm	70mm
主轴行程: Spindle Travel	100mm	100mm
旋径: Swing	410mm	410mm
主轴到工作台最大距离: Max. Distance spindle to table	320mm	320mm
主轴到底座最大距离: Max. Distance spindle to base	575mm	575mm
主轴锥度: Spindle Taper	MT2	MT2
转速范围: Speed Range	360~2700RPM	360~2700RPM
速度: No. of Speed	5	5
工作台尺寸: Table Size	283X248mm	283X248mm
底座尺寸: Base Size	520x345mm	520x345mm
机器总高: Overal Height	1040mm	1040mm
电机功率: Motor	380V/750W/50Hz	380V/750W/50Hz
重量: Weight	105KG	105KG
包装尺寸: Packing Size	750x430x950mm	750x430x950mm

工业级系列 INDUSTRIAL SERIES

Z1725F

型号: Model	Z1725F	ZS1725F
功能: Feature	Drilling	Drilling & Tapping
钻孔/攻丝范围: Drill/Tapping Capacity	25mm	25mm/M12
夹头: Chuck Capacity	1~16mm	1~16mm
立柱直径: Column Diameter	80mm	80mm
主轴行程: Spindle Travel	100mm	100mm
旋径: Swing	410mm	410mm
主轴到工作台最大距离: Max. Distance spindle to table	850mm	850mm
主轴到底座最大距离: Max. Distance spindle to base	1170mm	1170mm
主轴锥度: Spindle Taper	MT2	MT2
转速范围: Speed Range	360~2700RPM	360~2700RPM
速度: No. of Speed	5	5
工作台尺寸: Table Size	320X320mm	320X320mm
底座尺寸: Base Size	600x385mm	600x385mm
机器总高: Overal Height	1650mm	1650mm
电机功率: Motor	400V/750W/50Hz	400V/750W/50Hz
重量: Weight	130KG	130KG
包装尺寸: Packing Size	880x460x1830mm	880x460x1830mm

产品特写 KEY FEATURE

Tapping Device

Special Guard

工业级系列 INDUSTRIAL SERIES

优质高效与高性价比

- 立柱大尺寸 壁厚 运转平稳 性能稳定
- 主轴经热处理，精加工同心度高
- 可锁式主开关
- 钻夹头防护罩 高度可调节并带微动开关

- Heavy,solid cast iron construction
- Smooth running and stability due to a largely dimensioned thick-walled steel colomn
- High concentricity precision due to heat treatment and ground work spindle
- Lockable main switch and protective motor switch
- Height-adjustable screeing grid with micro switch

产品特写 KEY FEATURE

Tapping Device

Special Guard

Z2025B

型号: Model	Z2025B	ZS2025B
功能: Feature	Drilling	Drilling & Tapping
钻孔/攻丝范围: Drill/Tapping Capacity	20mm	20mm/M16
夹头: Chuck Capacity	3~16mm	3~16mm
立柱直径: Column Diameter	85mm	85mm
主轴行程: Spindle Travel	135mm	135mm
旋径: Swing	510mm	510mm
主轴到工作台最大距离: Max. Distance spindle to table	290mm	290mm
主轴到底座最大距离: Max. Distance spindle to base	570mm	570mm
主轴锥度: Spindle Taper	MT3	MT3
转速范围: Speed Range	250～2200RPM	250～2200RPM
速度: No. of Speed	5	5
工作台尺寸: Table Size	338X300mm	338X300mm
底座尺寸: Base Size	600x385mm	600x385mm
机器总高: Overal Height	1136mm	1136mm
电机功率: Motor	400V/1100W/50Hz	400V/1100W/50Hz
重量: Weight	170KG	170KG
包装尺寸: Packing Size	850x500x1030mm	850x500x1030mm

工业级系列 INDUSTRIAL SERIES

Z2032F

型号: Model	Z2032F	ZS2032F
功能: Feature	Drilling	Drilling & Tapping
钻孔/攻丝范围: Drill/Tapping Capacity	32mm	32mm/M16
夹头: Chuck Capacity	1~16mm	1~16mm
立柱直径: Column Diameter	99mm	99mm
主轴行程: Spindle Travel	135mm	135mm
旋径: Swing	510mm	510mm
主轴到工作台最大距离: Max. Distance spindle to table	730mm	730mm
主轴到底座最大距离: Max. Distance spindle to base	1145mm	1145mm
主轴锥度: Spindle Taper	MT3	MT3
转速范围: Speed Range	250～2200RPM	250～2200RPM
速度: No. of Speed	5	5
工作台尺寸: Table Size	420X380mm	420X380mm
底座尺寸: Base Size	650x440mm	650x440mm
机器总高: Overal Height	1740mm	1740mm
电机功率: Motor	400V/1100W/50Hz	400V/1100W/50Hz
重量: Weight	230KG	230KG
包装尺寸: Packing Size	940x520x1900mm	940x520x1900mm

产品特写 KEY FEATURE

Tapping Device

Special Guard

135mm Travel

Locking Device

4"×6" BELT AND DISC SANDER

BDS46

Key Features:

- Induction motor affords quiet and efficient power
- Cast iron base with robust steel construction
- Die-cast aluminum table for both horizontal and vertical operations At 0° ~45°
- Belt tension-release lever for the quick and easy belt changes
- Belt tracking system to guarantee the belt tracking
- Dust ejection port
- Precision 45° miter gauge facilicates the desired sanding angle

TMT BDS46 is a combination sanding machine with 4" x 36" sanding belt and 6" sanding disc.
With the powerful 1/3HP output built-in induction motor it provides efficient and smooth removal. The robust cast iron base affords sufficient stability during use to achieve consistent results with your desired amount of pressure. The die cast aluminum working table is universal for either the disc sanding horizontally or the belt sanding vertically at your most convenience, and it can tilt 0° to 45° at disc sanding to meet your working requirement. The belt sanding is adjustable to be positioned from 0° to 45° with a simple Alley Key, quick and simple. It is equipped with the belt tension release mechanism to make it quick and easy belt changes, and the belt trading knob helps to track the belt quickly to guarantee a safe and proper operation. It also comes with a compact miter gauge which can facilitate the precise angle sanding at the desired degree from 0° to 45° .

belt vertical sanding

belt tension quick release

precision miter gauge

belt tracking knob

Specification:

Belt Size	Disc Size	Table Size (mm)	Table Tilt (Disc Sanding)	Table Tilt (Belt Sanding)	Power HP
100x915 mm 4"x36"	150 mm 6"	150x228	0° ~45°	0° ~90°	1/3
Speed (Disc)	**Speed (Belt)**	**Net Weight**	**Gross Weight**	**Packaging Size**	**Loading/20FCL**
2850rpm	17 kg	18 kg	490m/min	550x265x290 mm	646 pcs

12" DISC SANDER

DS300

Key Features:

- 1 hp induction motor affords quiet and efficient power
- Overall robust cast iron construction
- Robust cast iron working table with the precision ground top surface Adjustable at 0° ~45°
- Double working table supports with angle indicator
- Simple and convenient table angle adjustment and locking mechanism
- Dust ejection port
- Manual brake to slow down the disc in a reasonable time
- Precision 45° miter gauge facilicates the desired sanding angle

TMT DS300 is an ideal choice in any hobbyist's workshop and it is a money saving machine with its compact and heavy duty design. The powerful 1HP induction motor offers the quiet and vigorous power through shaft drive transmission to ensure the most efficient and smooth results. With its overall robust cast iron construction and the cast iron working table, it can always provide the best stability under your desired pressure during operation and then achieve the satisfied results. The heavy duty cast iron working table has a finely ground top surface and a ground T-slot for the adjustable 45° miter gauge which is to facilitate the desired angle sanding and the end grain sanding. The working table can also tilt 45° upwards and downwards precisely with its unique table adjusting and locking mechanism underneath the table, the double table support system can afford both the precise angle adjustment and the stability to the table at any desired angle. The machine is also designed with a manual brake device which is to help stop the fast disc when power-off quickly or to lower the disc down in a reasonable time. A dust extraction system is designed from the bottom of the disc with a standard 63 mm diameter outlet, it is suitable for 60 mm diameter sleeve or hose for connecting to an extractor or dust collector.

table angle adjustment mechanism

table locking and indicator

miter gauge

manual brake

Specification:

Disc Size	Table Size mm	Table Tilt	Power HP	Speed (Disc) rpm	Net Weight kg	Gross Weight kg	Packaging Size mm	Loading 20FCL pcs
305 mm 6"	435×225	-45° ~0° ~45°	1	1420	34	36	530×460×430	270